



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Wuhan Newradar Special Gas Co., Ltd

ADDRESS: K6-3-1401 / 1402 ,

Wanda Global International Center office building ,

Wuchang District, Wuhan , Hubei, P.R. China

WEB SITE: www.highpuritygases.com

SUBSTANCE: AMMONIA, ANHYDROUS

TRADE NAMES/SYNONYMS:

MTG MSDS 4; ANHYDROUS AMMONIA; AMMONIA GAS; AMMONIA; SPIRIT OF HARTSHORN; AMMONIA, ANHYDROUS, LIQUIFIED; UN 1005; H3N; MAT01050; RTECS BO0875000

CHEMICAL FAMILY: inorganic, gas

2. COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT: AMMONIA, ANHYDROUS

CAS NUMBER: 7664-41-7

PERCENTAGE: 100.0

3. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=3 FIRE=1 REACTIVITY=0

EMERGENCY OVERVIEW:

COLOR: colorless

PHYSICAL FORM: gas, liquid

ODOR: pungent odor

MAJOR HEALTH HAZARDS: respiratory tract burns, skin burns, eye burns, mucous membrane burns

PHYSICAL HAZARDS: Containers may rupture or explode if exposed to heat.

POTENTIAL HEALTH EFFECTS:

INHALATION:



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

SHORT TERM EXPOSURE: burns

LONG TERM EXPOSURE: burns

SKIN CONTACT:

SHORT TERM EXPOSURE: burns

LONG TERM EXPOSURE: burns

EYE CONTACT:

SHORT TERM EXPOSURE: burns

LONG TERM EXPOSURE: burns

INGESTION:

SHORT TERM EXPOSURE: burns

LONG TERM EXPOSURE: burns

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

SKIN CONTACT: Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. Thoroughly clean and dry contaminated clothing and shoes before reuse. Destroy contaminated shoes.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

INGESTION: DO NOT induce vomiting. Never make an unconscious person vomit or drink fluids. Give large amounts of water or milk. When vomiting occurs, keep head lower than hips to help prevent aspiration. If person is unconscious, turn head to side. Get medical attention immediately.

NOTE TO PHYSICIAN: For inhalation, consider oxygen. For ingestion, consider esophagus copy. Avoid astric lavage.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Negligible fire hazard. Moderate explosion hazard. Containers may rupture or explode if exposed to heat.

EXTINGUISHING MEDIA: carbon dioxide, regular dry chemical
Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Do not get water inside container. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry. Stop flow of gas.

LOWER FLAMMABLE LIMIT: 15%

UPPER FLAMMABLE LIMIT: 28%

AUTOIGNITION: 1204 F (651 C)



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

6. ACCIDENTAL RELEASE MEASURES

AIR RELEASE:

Reduce vapors with water spray. Collect runoff for disposal as potential hazardous waste.

SOIL RELEASE:

Trap spilled material at bottom in deep water pockets, excavated holding areas or within sand bag barriers. Dike for later disposal. Add dilute acid. Absorb with sand or other non-combustible material.

WATER RELEASE:

Collect spilled material using mechanical equipment.

OCCUPATIONAL RELEASE:

Stop leak if possible without personal risk. Reduce vapors with water spray. Do not get water directly on material. Do not get water inside container. Keep unnecessary people away, isolate hazard area and deny entry. Small spills: Flood with water. Large spills: Dike for later disposal. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).

7. HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.111. Protect from physical damage. Store outside or in a detached building. Inside storage: Store in a cool, dry place. Store in a well-ventilated area. Avoid heat, flames, sparks and other sources of ignition. Keep separated from incompatible substances. Store in a cool, dry place. Store in a well-ventilated area. Notify State Emergency Response Commission for storage or use at amounts greater than or equal to the TPQ (U.S. EPA SARA Section 302). SARA Section 303 requires facilities storing a material with a TPQ to participate in local emergency response planning (U.S. EPA 40 CFR 355.30).

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

AMMONIA, ANHYDROUS:

50 ppm (35 mg/m³) OSHA TWA

35 ppm (27 mg/m³) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 25 ppm ACGIH TWA

35 ppm ACGIH STEL

25 ppm (18 mg/m³) NIOSH recommended TWA 10 hour(s)

35 ppm (27 mg/m³) NIOSH recommended STEL

VENTILATION: Provide local exhaust ventilation system. Ensure compliance with applicable



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

exposure limits.

EYE PROTECTION: Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

CLOTHING: Wear appropriate chemical resistant clothing.

GLOVES: Wear appropriate chemical resistant gloves.

RESPIRATOR: The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA.

250 ppm

Any chemical cartridge respirator with cartridge(s) providing protection against this substance. Any supplied-air respirator.

300 ppm

Any supplied-air respirator operated in a continuous-flow mode.

Any powered, air-purifying respirator with cartridge(s) providing protection against this substance. Any chemical cartridge respirator with a full facepiece and cartridge(s) providing protection against this substance.

Any air-purifying respirator with a full facepiece and a canister providing protection against this substance.

Any self-contained breathing apparatus with a full facepiece. Any supplied-air respirator with a full facepiece.

Escape -

Any air-purifying respirator with a full facepiece and a canister providing protection against this substance. Any appropriate escape-type, self-contained breathing apparatus.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: gas

COLOR: colorless

PHYSICAL FORM: gas, liquid

ODOR: pungent odor

MOLECULAR WEIGHT: 17.03

MOLECULAR FORMULA: N-H₃

BOILING POINT: -27 F (-33 C)

FREEZING POINT: -108 F (-78 C)

VAPOR PRESSURE: 6658 mmHg @ 21 C

VAPOR DENSITY (air=1): 0.5967

SPECIFIC GRAVITY: Not applicable

DENSITY: 0.7067 g/L @ 25 C

WATER SOLUBILITY: 38% @ 20 C

PH: 11.6 (1.0 N solution)

VOLATILITY: Not applicable

ODOR THRESHOLD: 1-5 ppm



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

EVAPORATION RATE: Not applicable

COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable

SOLVENT SOLUBILITY:

Soluble: methanol, ethanol, chloroform, ether, organic solvents



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

10. STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressure.

CONDITIONS TO AVOID: Minimize contact with material. Avoid inhalation of material or combustion

by-products. Containers may rupture or explode if exposed to heat.

INCOMPATIBILITIES: acids, combustible materials, metals, oxidizing materials, metal salts, halo carbons, halogens, amines, reducing agents, cyanides, bases

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: ammonia, oxides of nitrogen

POLYMERIZATION: Will not polymerize.

11. TOXICOLOGICAL INFORMATION

AMMONIA, ANHYDROUS:

TOXICITY DATA:

2000 ppm/4 hour(s) inhalation-rat LC50

LOCAL EFFECTS:

Corrosive: inhalation, skin, eye, ingestion

ACUTE TOXICITY LEVEL:

Toxic: inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: eye disorders, respiratory disorders, skin disorders and allergies

TUMORIGENIC DATA: Available.

MUTAGENIC DATA: Available.

12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

FISH TOXICITY: 1600 ug/L 96 hour(s) LC50 (Mortality) Common jollytail (Galaxias maculatus)

INVERTEBRATE TOXICITY: 7700 ug/L 96 hour(s) LC50 (Immobilization) Ark shell (Anadara granosa)

ALGAL TOXICITY: 2100-2300 ug/L NR hour(s) (Abundance) Algae, phytoplankton, algal mat (Algae)

PHYTOTOXICITY: 16500 ug/L 30 hour(s) (Abundance) Common water-nymph (Najas guadalupensis)

OTHER TOXICITY: 27200 ug/L 30 hour(s) LETH (Mortality) Frog (Rana sp)

13. DISPOSAL CONSIDERATIONS



AMMONIA, ANHYDROUS
MATERIAL SAFETY DATA SHEET

Dispose in accordance with all applicable regulations



AMMONIA, ANHYDROUS
MATERIAL SAFETY DATA SHEET

14. TRANSPORT INFORMATION

INTERNATIONAL U.S. DOT 49 CFR 172.101:

PROPER SHIPPING NAME: Ammonia, anhydrous

ID NUMBER: UN1005

HAZARD CLASS OR DIVISION: 2.3

LABELING REQUIREMENTS: 2.3; 8

QUANTITY LIMITATIONS:

PASSENGER AIRCRAFT OR RAILCAR: Forbidden

CARGO AIRCRAFT ONLY: Forbidden

ADDITIONAL SHIPPING DESCRIPTION: Toxic-Inhalation Hazard Zone D

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

SHIPPING NAME: Ammonia, anhydrous

UN NUMBER: UN1005

CLASS: 2.3; 8

15. REGULATORY INFORMATION

U.S. REGULATIONS:

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

AMMONIA, ANHYDROUS: 100 LBS RQ

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30):

AMMONIA, ANHYDROUS: 500 LBS TPQ

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40):

AMMONIA, ANHYDROUS: 100 LBS RQ

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):

ACUTE: Yes

CHRONIC: No

FIRE: No

REACTIVE: No

SUDDEN RELEASE: Yes

SARA TITLE III SECTION 313 (40 CFR 372.65):

AMMONIA, ANHYDROUS

OSHA PROCESS SAFETY (29CFR1910.119):

AMMONIA, ANHYDROUS: 10000 LBS TQ

STATE REGULATIONS:

California Proposition 65: Not regulated.

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION: A, E

NATIONAL INVENTORY STATUS:

U.S. INVENTORY (TSCA): Listed on inventory. TSCA



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

12(b) EXPORT NOTIFICATION: Not listed. CANADA

INVENTORY (DSL/NDSL): Not determined.



AMMONIA, ANHYDROUS

MATERIAL SAFETY DATA SHEET

16. OTHER INFORMATION

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).